



RE: TOWER SAFTY RULES

I, the undersigned agree to abide by the following rules as they relate to use of the Sway Mechanika training tower. I understand that failure to follow these rules may result in expulsion from property.

- Typical access to tower platform is by fixed rung ladder, fall protection to be provided by self- retracting lifeline mounted at top of climb
- All users will wear appropriate full body harnesses designed for rope access activities while on the tower
- Swing gate and midrail may be removed/opened only while performing the transition to platform from fixed ladder access
- Tower capacity: up to four (4) attendees maximum at any one time
- Approved tie off/anchorage points for suspension and/or fall arrest include the perimeter pipe rail, midpoint anchor rings, and D rings mounted on the column heads
- The perimeter mid rail is provided with a pre-engineered load limiting energy absorber, and capacity of 4 for fall restraint, or 2 for fall arrest purposes. The midrail shall be connected to when entry gate is opened, and for the transition to ladder
- The midrail/HLL shall incorporate connections to the blue rigging pears or the cable directly with compatible connectors (no locking snap hook use)
- Horizontal aid points consist of three swaged wire rope basket assemblies used to laterally progress across beam
- Vertical aid points are installed on the NE tower leg, and are spaced at 1.5 foot intervals, per SPRAT requirements
- A mid height deviation anchorage is installed at the southern column
- Wire rope guying system shall be checked daily prior to use of the tower, and by Sway Mechanika personnel
- No horseplay, or use under the influence of any substance that impairs good judgement, physical ability, or creates an unsafe condition
- Highlines, sloped tyroleans, skate systems, or other lateral loading is to be reviewed by SM prior to application. Additional directional guys may be required to accommodate this type of loading
- Hardhats shall be worn when trainings are in progress, or when in general vicinity of overhead hazards
- Users shall have the ability and training to effect a rescue promptly, SM provides a 28 foot ladder if needed at all times when tower use is ongoing. First aid supplies and training to be provided by users
- Material hoist davit at NE column is limited to 50 lbs, and is NOT rated for life support
- No unauthorized person may use this tower without acknowledgement of the above mentioned mandates.

Signed/dated